



EP 1522

Bench with backrest

SPECIFICATIONS

Supports:	10mm X 102mm (3/8" X 4") steel flat and 76mm X 76mm (3" X 3") steel tube
Contour straps (3):	10mm X 51mm (3/8" x 2") steel flat
Armrests (2):	6mm X 51mm (1/4" X 2") steel flat
Finish:	Hot-dipped galvanized
Slats:	RPU/DFP 38mm X 64mm (1 1/2" X 2 1/2") & bullnose 38mm X 84mm (1 1/2" X 3 5/16") JAT/WOA 25mm X 64mm (1" X 2 1/2") & bullnose 25mm X 84mm (1" X 3 5/16")
Fasteners:	Hot-dipped galvanized

COVERINGS

YRPU	Grey recycled plastic	DFP	Select Douglas fir
SRPU	Sand recycled plastic	JAT	Jatoba
ORPU	Olive recycled plastic	WOA	White oak
CRPU	Cedar recycled plastic		
WRPU	Walnut recycled plastic		

OPTIONS

A	Painted armrests (2)
AS	Painted anti-skate
CA	Painted central armrest
P	Galvanized and painted frame

Depth: 617mm (24 1/4") Length: 1803mm (71") Height: 856mm (33 7/8") Weight: 90 kg (198 lb)

This bench must be anchored.

CONCRETE SLABS AND ANCHORS

	1 slab 610mm X 1829mm X 152mm (24" X 72" X 6")
	1 slab 1067mm X 1829mm X 152mm (42" X 72" X 6")
	2 slabs 305mm X 711mm X 152mm (12" X 28" X 6")
QS-HDI	4 drop-in anchors with stainless steel hex head bolts
QAV	4 drop-in anchors with stainless steel theftproof bolts
HVA	4 adhesive anchors with stainless steel threaded rods and theftproof nuts

Confidential information contained herein is the property of Equiparc. Intended use is limited to professionals specifying Equiparc's products and their direct clients. All information is not to be copied or disclosed to others without the written consent of Equiparc. All rights reserved - Equiparc Manufacturier d'Equiptement de Parcs Inc.