



EP 1600-5

Bench with backrest

SPECIFICATIONS

Supports:	Cast aluminum
Contour strap:	Aluminum flat
Reinforcement (2):	Galvanized 25mm X 25mm (1" X 1") steel tube (plastic only)
Finish:	Polyester powder coated
Slats:	RPU/DFP 38mm X 64mm (1 1/2" X 2 1/2") JAT/WOA 25mm X 64mm (1" X 2 1/2")
Fasteners:	Hot-dipped galvanized

COVERINGS

YRPU	Grey recycled plastic	DFP	Select Douglas fir
SRPU	Sand recycled plastic	JAT	Jatoba
ORPU	Olive recycled plastic	WOA	White oak
CRPU	Cedar recycled plastic		
WRPU	Walnut recycled plastic		

OPTION

A	Painted armrests (2)
---	----------------------

Depth: 661mm (26") Length: 1499mm (59") Height: 802mm (31 5/8") Weight: 69 kg (152 lb)

This bench must be anchored.

CONCRETE SLABS AND ANCHORS

	1 slab 610mm X 1525mm X 152mm (24" X 60" X 6")
	1 slab 1067mm X 1525mm X 152mm (42" X 60" X 6")
	2 slabs 305mm X 711mm X 152mm (12" X 28" X 6")
QS-HDI	4 drop-in anchors with stainless steel hex head bolts
QAV	4 drop-in anchors with stainless steel theftproof bolts
HVA	4 adhesive anchors with stainless steel threaded rods and theftproof nuts

Confidential information contained herein is the property of Equiparc. Intended use is limited to professionals specifying Equiparc's products and their direct clients. All information is not to be copied or disclosed to others without the written consent of Equiparc. All rights reserved - Equiparc Manufacturier d'Equipement de Parcs Inc.