



EP 1660-5

Bench with backrest

SPECIFICATIONS

Supports: Cast aluminum

Contour strap (2): Steel flat

Bracing plates (3): 1524mm (5') steel flat on 3 slats (plastic only)

Reinforcement (2): Steel flat

Finish: Polyester powder coated

Slats: RPU/DFP 38mm X 64mm (1 1/2" X 2 1/2")

JAT/WOA 25mm X 64mm (1" X 2 1/2")

Fasteners: Zinc plated

COVERINGS

YRPU Grey recycled plastic DFP Select Douglas fir

SRPU Sand recycled plastic JAT Jatoba
ORPU Olive recycled plastic WOA White oak

CRPU Cedar recycled plastic WRPU Walnut recycled plastic

Depth:603mm (23 3/4") Length:1466mm (57 3/4") Height:840mm (30") Weight:64 kg (142 lb)

This bench must be anchored.

CONCRETE SLABS AND ANCHORS

1 slab 610mm X 1829mm X 152mm (24" X 72" X 6")

1 slab 1067mm X 1829mm X 152mm (42" X 72" X 6")

2 slabs 305mm X 711mm X 152mm (12" X 28" X 6")

QS-HDI 4 drop-in anchors with stainless steel hex head bolts
QAV 4 drop-in anchors with stainless steel theftproof bolts

HVA 4 adhesive anchors with stainless steel threaded rods and theftproof nuts

Confidential information contained herein is the property of Equiparc. Intended use is limited to professionals specifying Equiparc's products and their direct clients. All information is not to be copied or disclosed to others without the written consent of Equiparc. All rights reserved - Equiparc Manufacturier d'Equipement de Parcs Inc.