



EP 1660

Bench with backrest

SPECIFICATIONS

Supports:	Cast aluminum
Contour strap:	Steel flat
Bracing plates (2):	Steel flat
Finish:	Polyester powder coated
Slats:	DFP 38mm X 64mm (1 1/2" X 2 1/2") JAT 25mm X 64mm (1" X 2 1/2")
Fasteners:	Zinc plated

COVERINGS

DFP	Select Douglas fir (Wood)
JAT	Jatoba (Wood)

Dept : 603mm (23 3/4") Length: 1847mm (72 3/4") Height: 840mm (33") Weight: 42 kg (92 lb)

This bench must be anchored.

CONCRETE SLABS AND ANCHORS

	1 slab 610mm X 2032mm X 152mm (24" X 80" X 6")
	1 slab 1067mm X 2032mm X 152mm (42" X 80" X 6")
	2 slabs 305mm X 711mm X 152mm (12" X 28" X 6")
QS-HDI	4 drop-in anchors with stainless steel hex head bolts
QAV	4 drop-in anchors with stainless steel theftproof bolts
HVA	4 adhesive anchors with stainless steel threaded rods and theftproof nuts

Confidential information contained herein is the property of Equiparc. Intended use is limited to professionals specifying Equiparc's products and their direct clients. All information is not to be copied or disclosed to others without the written consent of Equiparc. All rights reserved - Equiparc Manufacturier d'Equiptement de Parcs Inc.

DESIGN DURABILITY EXPERTISE

1001 James-Brodie Street, Saint-Jean-sur-Richelieu, Québec J2X 0C1 Canada
Tel.: 450 346-1882 1 800 363-9264

info@equiparc.com | equiparc.com